


"CAT-2-TA"

Heavy-Duty Label Rewinders with Tension Arm


The **CAT-2-TA** is a **CAT-2** with tension arm specially engineered for applications that require fixed web tension. LABELMATE's **Constant Adjustable Torque™ ("CAT")** technology has made the silent, easy-to-use **CAT-2** the "Industry Standard" Label Rewinder.

IMPORTANT NOTE: The **CAT-2-TA** can be also be used as a regular **CAT-2** with the same features.




The standard **CAT-2-TA** handles labels up to 155 mm (6-inches) wide and will wind a roll of labels up to a 220 mm (8.7") diameter. Torque and Direction are fully controllable from the Control Panel.

For wider labels up to 255 mm (10"), choose the **CAT-2-TA-10"**.




Model **CAT-2-TA-ACH** includes an Adjustable Core Holder that accepts any core size from 25 mm to 101 mm (1-inch to 4-inches) in diameter and up to 155 mm (6-inches) in width.

The optional Adjustable Paper Guide **APG-CAT** with movable arm can be installed in minutes on the base of the **CAT-2-TA-ACH** or **CHUCK**. This inexpensive accessory guides the outer edge of the label roll as it's being rewound to ensure even roll alignment.



The **CAT-2-TA-CHUCK** includes LABELMATE's durable "Quick-Chuck™" quick-locking Core Chuck, permitting the fastest loading and unloading of cores and label rolls. The **CAT-2-TA-CHUCK** is ideal for high-volume production environments, or anywhere the ultimate convenience in Rewinders is desired. The **CAT-2-TA-CHUCK** is available for 38-,40-,44-,70, 76- and 100 mm cores.



The **CAT-33-TA** accepts bigger rolls with a diameter up to 330 mm. It is equipped with the LABELMATE "Quick-Chuck™" quick-locking Core Chuck.

All CAT-2-TA are coming with a Heavy-Duty Power Supply.

Rugged, heavy-gauge steel construction allows your **CAT-2-TA** Rewinder to be simply set in place. Special anti-slip feet keep the unit from moving. Reliable, high quality and maintenance-free, the Heavy-Duty **CAT-2-TA** Label Rewinders feature a **3-Year Parts and Labour Limited Warranty**, the longest in the industry. Put LABELMATE **CAT-2-TA** Label Rewinders to work for you today and enjoy a new dimension in label rewinding convenience and reliability. Custom colours, badging, and special core holders are available for private label applications.

See Page 2 for available models and specifications.

Full Size "CAT-2-TA" Heavy-Duty Label Rewinders with Tension Arm

MODEL	ADD SUFFIX	DESCRIPTION	WIDTH	DIAM.	SPEED
CAT-2-TA	CHUCK	The industry standard Heavy-duty Label Rewinder with an easy-loading 'Quick-Chuck'. Ideal for production work. 76 mm (3") standard*.	Up to 170 mm (6,5")	Up to 220 mm (8.7")	Up to 76 cm/s (30 ips, inches per second)
	STANDARD	The 'Industry Standard' Heavy-duty Label Rewinder. 76 mm (3") standard*.	Up to 155 mm (6")	Up to 220 mm (8.7")	
	1-INCH	CAT-2-TA for 25 mm (1") diameter cores.	Up to 155 mm (6")	Up to 220 mm (8,6")	
	10-INCHES	CAT-2-TA for labels up to 255 mm wide. 76 mm (3") standard*.	Up to 255 mm (10")	Up to 220 mm (8.7")	
	ACH	CAT-2-TA with an Adjustable Core Holder for any core size from 25 to 101 mm in diameter. With inner flange. Use APG-CAT if you wish to also guide the outer edge of your label.	Up to 155 mm (6")	Up to 220 mm (8.7")	
CAT-33-TA	-	Tight rewind up to 330 mm. 76 mm (3") 'Quick-Chuck' standard*.	Up to 170 mm (6,5")	Up to 330 mm (13")	
ADAPT-326	-	Adapter for 76mm CAT-2-TA-CHUCK allows use of 152 mm diameter cores (6").	-	-	-
APG-CAT	-	Optional Adjustable Paper Guide For CAT-2-TA-ACH or CAT-2-TA-CHUCK. Guides the outer edge of the label web to ensure an even roll edge.	-	-	Installs in minutes
VANES	-	Set of 3 vanes (fins). 38, 40, 44, 70 & 76 mm available	-	-	-
ACH-CAT-S	-	Adjustable Core Holder for any core size from 25 to 100 mm (1" to 4") in diameter. With inner flange.	Up to 155 mm (6")	Up to 220 mm (8.7")	-
HD-PS		230V – 50Hz DC Heavy-Duty Power Supply. Output: 14V – 4.6A	-	-	-

* The CAT-2-TA-CHUCK, Standard, CAT-33-TA and 10-Inches are available for 38-, 40-, 44-, 70-, 76- and 100 mm (CHUCK only) diameter cores.

CAT-2-TA SPECIFICATIONS:

All models are bi-directional.

"TORQUE ADJUST" - Continuously adjustable torque and braking control

"TORQUE RANGE" - NORMAL, HIGH

"EXTERNAL HALT CONTROL" - External control removes power to the motor and applies braking.

Dimensions: 324H x 381W x 318D mm (12.75H x 15W x 12.5D").

Base plate footprint: 180 x 370 mm (7 x 15") or 180 x 280 mm (7 x 11")

Weight: Approximately 10.5 to 12.7kg (23- to 28-lbs)

Power Requirements: 230-vac 50-Hz. 40-v. 120-vac 60-Hz power supply is also available at the same price.

Warranty: 3-Year Parts and Labour Limited Warranty, the longest in the industry.

(One-Year Limited Warranty on included Power Supply Module.)

Specifications are subject to change without notice. DATACAT2TA EUR.DOC 09/2004

The World's Leading Manufacturer of Label Rewinders, Unwinders, Dispensers, Slitters and Core Chucks
LABELMATE EUROPE, 69 AVENUE ALPHONSE XIII, B-1180 BRUSSELS, BELGIUM
+32 (2) 375-6960 FAX +32 (2) 375-3896 www.labelmate.com E-mail : brussels@labelmate.com
LABELMATE LLC, 12A SUNSET WAY, HENDERSON, NV 89014-2002 USA
Toll-Free! (877) 833-7149 (702) 435-8535 FAX (702) 435-8536 E-mail: info@labelmate.com