



Competitive ribbon for all labeling applications

Applications

- Rack identification labels
- Produce labels
- Tote and crate labels
- Building material labels
- Medical device labels
- Cosmetics packaging labels
- Clothing tags
- Retail labels
- And many more...



Key benefits

- Very good printing quality
- Prints on all label substrates
- Ideal for rough label substrates

Recommended substrates

Rough papers	● ● ● ● ● ●
Coated papers/tags	● ● ● ● ● ●
Synthetics	● ● ● ● ○ ○
Packaging films	● ● ● ● ○ ○

Print quality

0° barcode	● ● ● ● ● ●
90° barcode	● ● ● ● ● ○
Small characters	● ● ● ● ● ○

Print resistance

Abrasion	● ● ● ● ○ ○
Solvent	○ ○ ○ ○ ○ ○
Heat	100°C 212°F

Printer parameters

Maximum speed: 16 ips (400 mm/s)

Heat settings:



Technical specifications

- Film thickness: 4,5µm
- Total ribbon thickness: <8µm
- Ink melting point: 80°C | 176°F
- Coefficient of friction: Kd < 0,2
- Ink blackness: 1,8 ODR
- Antistatic designed

Approvals

- REACH / SVHC 1907/2006/EC
- EU Food Contact 1935/2004/EC
- US Food Contact FDA
- RoHS / Heavy Metals 2011/65/EU
- California Proposition 65

Storage conditions

- 12 months recommended
- 20-80% Relative Humidity
- 5-35°C (40-95°F) temperature